



100 Royal Way
 Temple, GA 30179
 Phone (800) 520-6593

SPECIFICATION DATA SHEET

Date:10/16/2007

MODEL No. 505
Top Outlet Insulated Box

DIMENSIONAL DATA:

<u>Register</u>		<u>R4 Insulation</u>	<u>R6 & R8 Insulation</u>
<u>Size</u>	<u>Collar Size</u>	<u>Actual Dimensions</u>	<u>Actual Dimensions</u>
8x4	4,5	10x6	11x7
10x4	4,5,6	12x6	13x7
10x6	4,5,6,7,8	12x8	13x9
12x4	6,7	14x6	15x7
12x6	6,7,8	14x8	14x9
14x6	6,7,8,9	16x8	17x9

FABRICATION DATA:

Material:
 ASTM-A653 CS Type B Galvanized Steel,
 G-30 Coating LFQ Chemical Treatment

Assembly:
 Ceiling Boot assembled with 1/8" x 5/32" Zinc Coated Steel Rivets, has a rectangular opening with a 1" 90 deg Outboard Flange and 1/2" Drywall Flange. The collar is 3 1/2" tall roll formed 30GA Steel with 1/4" roll formed beading.

Insulation:
 Linacoustic RC manufactured by Johns Manville.
 Available Thickness: R4 - 1", R6 - 1 1/2", & R8 - 2"
 Specs available upon request

OPTIONS

505D: With Damper
 505R6S: R6 Insulation with sealed with mastic

